

Floor Graphic Markers

Half Circles - 750mm Wide



Features and Benefits

- Large 750mm wide x 375mm deep floor markers
- Ultra-low (0.45mm thick) helps prevent pallets catching
- Super strong adhesive quality
- Slip-resistance tested to R9 standard
- Highlights the area to keep clear in front of fire doors to ensure safety
- Available in 12 text designs and 8 non-text designs



These large anti-slip floor markers can be used on any flat, sealed surface. Ideal for use in front of fire exit doors, to highlight fire extinguisher areas or to warn/highlight any important messaging. The slimline markers feature an aggressive, permanent adhesive suitable for busy industrial environments - offering quick and easy installation compared to traditional marking methods - whilst remaining extremely wear resistant.

Material Specification

Adhesive

80 micron Polymeric White PVC film Permanent & Grey adhesive
 Double-side PE Coated
 Liner Up to 5 years durability
 Fire Certification - Class B. BS EN 13501-1:2007
 Anti-slip laminate tested to R9 standard.

Property	Specification	Test Method
Thickness (Including adhesive)	105µm ± 10%	Micrometer
Tensile strength	> 1.8kg/cm	ASTM 882
Elongation	> 100%	ASTM 882
Peel adhesion(24hrs)	> 1,500g/in	180 peeling PSTC-1
Application temp.	> 10°C	18 to 25°C optimum, on clean substrate
Gloss : LD3911G	60 ↑	@60, in machine direction
Gloss : LD3911M	20 ↓	(ASTM D 2457)
Dimensional stability	Max 0.5mm	Adhered to aluminum plate, Length direction (100°C oven, 2hr , average)
Release liner thickness	0.14mm ± 10%	Micrometer