

frames4floors[®]

A4 and DL Size

**Features and Benefits**

- Flat, colour coded floor identification frames
- Available in 2 insert sizes: A4 and DL
- Choice of 6 stand out colours
- Permanent industrial strength adhesive to withstand warehouse traffic
- Ideal for identifying bulk stack locations or to highlight important information

Material Specification

Rigid Matt PVC 200 micron
Black, yellow, red, green, blue and
Black/yellow diagonal hazard.

Adhesive

Acrylic Pressure Sensitive
Adhesive

The Adhesive is a high performance water based pressure sensitive adhesive.

It has very high adhesion and tack, whilst retaining reasonable elevated temperature performance.

Suitable for application onto a clean, flat, sealed surface.

Properties	Standard	Units	Values	
Thickness	EN I 1849-2 (Micrometer)	μ	200 = +/-8%	
Tensile stress at break	EN ISO 527-3(200mm/min)	MPa	Longitudinal	>43
			Transverse	>37
Tensile strain at break	EN ISO 527-3(200mm/min)	MPa	Longitudinal	>127
			Transverse	>97
Shrinkage	DIN 53377(10 min;+80°C)	%	<-5,0	
Slip assessment: dry	Pendulum test @45° and 90°	PTV	Low slip risk 64 median	

*NB All wet floors are hazardous so slip risk when wet not specified.
NB Figures are for 30gsm coatings on 50 micron polyester film.*

Typical Properties

Solids content	52%
Viscosity (spindle 4, speed 20 rpm)	1500 cps
Brookfield RVT type viscometer	
Adhesion to Stainless Steel (20 Mins)	25 N/25mm
FINAT FTM1	
Loop Tack to Stainless Steel	18 N/ 25mm FINAT FTM9
Static Shear (1Kg 25 x 25mm)	8 Hour
FINAT FTM8	