

## Stock Identity Slider



### Features and Benefits

- System to show stock availability
- Aggressive adhesive fixing
- Slider is 30mm high x 100mm wide
- Ideal for use on racking and shelving

Our 2 colour stock indicator slider has a permanent aggressive adhesive fixing and is simple to use. Helps to instantly show where products are running low without the need to view inside boxes. The white slider can be written on (or affix a label) with the product code or stock locations to help identify the stored product.



### Material Specification

#### Slider Base Product

PVC extrusion  
 1.0mm thick average

#### Magnetic Slider

Isotropic Magnetic Extrusion of strontium ferrite in a synthetic rubber binder and magnetized multi-pole on one face. Attached by adhesive detailed right.

Temperature range:  
 -30°C to 55°C (above 50°C magnetic losses occur).

Slider	Test Method	Units	Base
Tensile strength at yield	ISO 527	N/mm <sup>2</sup>	44
Flexural Strength	ISO 178	N/mm <sup>2</sup>	2800
Vicat Softening Point (5kg-50C/h)	ISO 75	°C	80
Density	ISO 1183	g/cc	1.38 +/-0.03
Flammability rating @ 1.0mm	UL 94	Class	V-1

Product	Indicator Slider
Adhesive type	Acrylic
Carrier	Polyester film
Thickness	0.22mm
Peel adhesion @ 23°C	20N/20mm
Temperature range	-30°C to 175°C